

## Declaration of Performance

No. DOP\_LS5N01\_179

**1. Identification code of product type**

**Mortise lock series LS5N including the models: LS5N04xx, LS5N05xx and LS5N15xx**

**2. Name and address of the manufacturer**

Salto Systems S.L. (c/Arkotz, 9 - 20180 Oiartzun – Spain - CIF B20708517)

**3. Intended use of the construction product**

Emergency exit devices operated by a lever handle for doors in escape routes.

**4. System of assessment and verification of constancy of performance: System 1**

**5. Notified body 1239 TECNALIA R&I Certificación, S.L.** performed initial tests, initial manufacturing plant inspection and surveillance, assessment and continuous approval of factory production center, under System 1 and issued the conformity certificate 1239/CPR/0815101

**6. Declared performance**

| Essential characteristics*               | Performance |  | Harmonised technical specification |
|--|-------------|--|------------------------------------|
| *Category of use                         | 3           | High frequency of use and misuse               | EN 179: 2008                       |
| *Durability                              | 7           | 200.000 cycles                                 |                                    |
| Door mass                                | 6           | ≤200 kg  |                                    |
| *Suitability for use on fire/smoke doors | B           | Suitable for use on fire/smoke resisting doors |                                    |
| People Safety                            | 1           |  |                                    |
| Corrosion resistance                     | 3           | High corrosion resistance (96h)                |                                    |
| Security                                 | 3           | 2000 N   |                                    |
| Lever projection                         | 2           | ≤100 mm  |                                    |
| Operation type                           | A           | Emergency exit devices operated by lever       |                                    |
| Application field                        | B/D         | One leave door opening outwards / inwards      |                                    |

**7. The performance of the product identified in point 1, is in conformity with the declared performance in point 6.**

This declaration of performance is issued under the sole responsibility of the manufacturer identified in



point 2.Oiartzun, 2015/11/02

Juan Imedio  
R&D Director